

MAICO Audiometer MA 25

Light and independent for basic screening

Sleek and Small Design

The super-lightweight MA 25 weighs in at only 980 g. Small enough to hold in the palm of your hand! Tucked into its carrying case, the MA 25 is one of our smallest, lightest portables.

Accurate and Dependable Engineering

Because it is portable, the MA 25 has been engineered to be tough and reliable. Take the MA 25 everywhere with confidence. User-friendly knobs make adjusting frequency and hearing levels easy and comfortable!

Full Range of Test Options

The MA 25 offers a full range of testing opportunities. Frequencies range from 125 Hz to 8000 Hz and signal intensities run from -10 dB HL to 100 dB HL. Pure and warble tone (pulsed and continuous) make it complete.

Compatible to Sessions: Get ready for fast data transfer!

Use the MA 25e with our intuitive data transfer solution Sessions, for easy management and visualization of your audiograms.

Features at a Glance

- Air conduction audiometer
- 11 frequencies from 125 Hz to 8000 Hz
- Test signals from -10 dB HL to 100 dB HL
- Pure tone and warble tone (pulsed or continuous)
- Portable and lightweight, only 980 g
- Use with 3 AA batteries, power supply or USB cable to PC
- MA 25e version including automated Hughson-Westlake test, talk forward and MAICO Sessions PC Software connectable with OtoAccess® or Noah patient database for easy data management
- Optional carrying case



Technical Data


MA 25 SPECIFICATIONS

Test Signals	Pure tone and warble tone (pulsed and continuous)
Test Frequencies	125, 250, 500, 750, 1000, 1500, 2000, 3000, 4000, 6000, 8000 Hz
Level Steps	5 or 1 dB
Hearing Level Range AC	-10 dB HL to 100 dB HL

DEVICE GENERAL

Dimensions	W x D x H: 22.5 cm x 18 cm x 5.5 cm
Weight	980 g including standard components
Power Supply	3 AA batteries or optional power supply (100-240 VAC ± 10 %, 50/60 Hz, 0.6 A)
Display	38.1 mm x 50.8 mm, monochrome
Language	English, Dutch, French, German, Italian, Spanish

STANDARDS

Safety	IEC 60601-1: 2012 AAMI ES60601-1:2005+A2+A1 CAN/CSA-C22.2 No. 60601-1:14 Type B applied parts
EMC	IEC 60601-1-2:2014
CE0123	 Class IIa according to Medical Device Regulation (EU) 2017/745
Audiometer	IEC 60645-1:2017 Type 4 ANSI/ASA S3.6-2018 Type 4

STANDARD COMPONENTS

- AC headset DD45
- 3 AA batteries
- Audiogram Pad

OPTIONAL TRANSDUCER

- AC noise-enclosure headset DD65 v2

OPTIONAL ACCESSORIES

- Patient response switch
- Carrying case
- Power supply

MA 25E VERSION

Special Tests	Automated Hughson-Westlake
Additional Accessories	<ul style="list-style-type: none"> • Patient response switch • USB cable
Software	MAICO Sessions PC Software
Optional Software	<ul style="list-style-type: none"> • OtoAccess® Database • OtoAccess® Worklist HL7 (OtoAccess® Database add-on) • Noah Database

Specifications are subject to change without notice.

**Standard
Components**



MA 25 device



AC headset DD45



Audiogram pad

**Optional
Accessories/
Software**



AC headset DD65 v2



Patient response switch



Carrying case



MAICO Sessions PC Software



OtoAccess® Database



Noah Database

MAICO Diagnostics GmbH

Sickingenstr. 70-71 · 10553 Berlin · Germany
 Tel.: +49 30/70 71 46-50 · Fax: +49 30/70 71 46-99
 sales@maico.biz · www.maico.biz

MEDICARE AG

Hauptstrasse 51 CH-5024 Küttigen
 Tel.: +41 44 482 482 6 Fax: +41 44 482 74 88
 info@medicareag.ch www.medicareag.ch